

Sonaca PVC accessories



SONACA PVC fittings are produced by means of injection molding, which consists of mixing and plasticizing of a PVC compound designed to be injected at high pressure. Once plasticized, the compound is injected hydraulically into metallic molds in which cavities form of the desired piece shape.

SONACA PVC fittings are the ideal compliment for our PVC pipes. They will also fit any other manufacturer's pipes made to corresponding ASTM standards. We offer two ranges : SCH-40 pressure and thin-wall DWV. They are used for the transport of fluids, vents, drainage, etc. They are available from 1/2" to 4" in diameter in a variety of shapes.

Among the benefits of the use of the PVC Sonaca pieces we can point out:

- Quick and easy installation
- No special tools is required for the installation
- They are profitable when compared with metallic pieces
- Excellent flow characteristics
- Smooth interior wall
- Easy to carry and transport.

We fulfill the strictest levels of qualities according to the ASTM international standards, in order to ensure that our consumers have the confidence to use our brand.

Technical Specifications:						
	Quantity per box	Description	Total weight	Work pressure	Quality Standard	Main use
	1000	Male Adapter 1/2" Pressure	32	600 PSI	D2466	Joining pipes to pieces with female adapters
	600	Male Adapter 3/4" Pressure	26	480 PSI	D2466	
	300	Male Adapter 1" Pressure	22	450 PSI	D2466	
	84	Male Adapter 1 1/2" Pressure	13	330 PSI	D2466	
	48	Male Adapter 2" Pressure	10	280 PSI	D2466	
	12	Male Adapter 3" Pressure	8	260 PSI	D2466	
	8	Male Adapter 4" Pressure	8	220 PSI	D2466	
	Quantity per box	Description	Total weight	Work pressure	Quality Standard	Main use
	700	Female Adapter 1/2" Pressure	29	600 PSI	D2466	Joining pipes to pieces with male adapters
	400	Female Adapter 3/4" Pressure	22	480 PSI	D2466	
	308	Female Adapter 1" Pressure	28	450 PSI	D2466	
	54	Female Adapter 1 1/2" Pressure	9	330 PSI	D2466	
	33	Female Adapter 2" Pressure	7	280 PSI	D2466	
	12	Female Adapter 3" Pressure	8	260 PSI	D2466	
	8	Female Adapter 4" Pressure	8	220 PSI	D2466	
	45	Female Adapter 3" Pressure	23	260 PSI	D2466	
24	Female Adapter 4" Pressure	17	220 PSI	D2466		

